

## FF BD600 (TX7130) CONVENTIONAL BEAM DETECTOR



EN54-12 CPR CE 

### FEATURES

- ▶ Large coverage
- ▶ Smooth operation between 5-100 meters
- ▶ Unmatched suitability for smoke detection
- ▶ Adjustable detector sensitivity
- ▶ Receiver and transmitter in a slot
- ▶ Possibility of economical wiring
- ▶ Laser Alignment Guide
- ▶ EN54-12 Certified
- ▶ LPCB Approved
- ▶ CPR Certificated

### TECHNICAL SPECIFICATIONS

- |                               |                    |
|-------------------------------|--------------------|
| ▶ Operating Voltage           | 20V ~ 28V DC       |
| ▶ Operating Current           | ≤23mA              |
| ▶ Operating Alarm Current     | 33mA               |
| ▶ LED display                 | Red, Yellow, Green |
| ▶ Relay Output (Fire / Fault) | Normal Open        |
| ▶ NO Contact                  | 2A 30V DC          |
| ▶ Operating Temperature       | -5 °C ~ + 55 °C    |
| ▶ Storage Temperature         | -5 °C ~ + 55 °C    |
| ▶ Humidity                    | ≤95%               |
| ▶ Size                        | 191x127x92 mm      |

### ORDER DETAILS

- ▶ FF BD600 (TX7130) Conventional Beam Detector